

CHRYSLER

N40L1

ARB DELUXE BULL BARS & WINCH BARS

Including Air Bag Equipped Models

YearTypeFeaturesWinchesMinchesPart No.1993-98Winch BarAirbag Approved, Recessed Indicators, Tow Points,HS9500, XD9000,3450060

M8000, M6000

IPF LIGHTS & LIGHTING ACCESSORIES

Year Recommended Lighting

1993-98 800XSD, 900XS, 900HID, 930 S/R, 960 S/R, 868CS, 968CS, J-01

SAFARI SN	ORKELS								
<u>Year</u>	Recommended	Snorkel							
1993-98	All V8 Models,	4.0 I6 Models ¹				SS1120HF			
	¹ 1993-95 Inline 6 (4.0L) models require the relocation of the PCM and additional installation steps.								
OLD MAN E	MU SUSPENSION	N PRODUCTS							
Model	Location	Description	Type	Lift	Quantity	Part No.			
4.0L 6cyl	Front	Stock.Light Load (0-80lbs)	Spring	1.0"	2	OME931			
			Shock		2	*N39/N39C			
4.0L 6cyl	Front	Medium Load (80-160lbs)	Spring	.75"	2	OME930			
			Shock		2	*N39/N39C			
5.2L V8	Front	Stock.Light Load (0-90lbs)	Spring	1.0"	2	OME934			
			Shock		2	N39			
5.2L V8	Front	Heavy Load (90-180lbs)	Spring	.75"	2	OME934			
			Shock		2	N39			
ALL	Rear	Medium Load	Spring	1.0"	2	OME940			
			Shock		2	*N40/N40C			
ALL	Rear	Heavy Constant Load (220lbs +)	Spring	.75"	2	OME943			
					2	N40			
	Complete Kit	ZJ 4.0L Stock/Light Load	Kit		1	OMEZ6CYLLK			
		ZJ 4.0L Heavy Load	Kit		1	OMEZ6CYLHK			
		ZJ V8 Stock Light Load	Kit		1	OMEZJ8CYLLK			
		ZJ V8 Heavy Load	Kit		1	OMEZJ8CYLHK			
	Installation	Steering Damper			1	OMESD40			
	Optional	Front 10mm Trim Packer				OMEJGF10			
		Rear 10mm Trim Packer				OMEJGR10			
	Also Available	Front Extended Length Shocks	·		2	N39L ¹			
					_				

¹ N39L/N40L Extended length shocks are for 3-5" suspension llfts only and are not intended for use with any Old Man Emu systems. Modified bump stops are required.

Rear Extended Length Shocks

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES						
Year	<u>Axle</u>	<u>Description</u>	Shaft	Spline	Ratio	Part No.
1993-98	Front	Dana 30	29.5 (1.16")	27	3.73 & UP	RD100 ¹
					3.54 & DN	RD101 ¹
				30	3.73 & UP	RD104
1993-98	Rear	Dana 35, C-clip, XJ, YJ, ZJ, TJ, WJ	29.5 (1.16")	27	2.73-3.31	RD103 ²
					3.54 & UP	RD102 ²³
				30	3.54 & UP	RD105

Quadradrive traction control vehicles require non-quadradrive axle shaft replacements for Air Locker installation.

^{*} ARB Air Locker does not fit Dana 44 Aluminum housing.*

ARB AIR LO	CKER DIFFERENTIAL COVERS	
Differential	Description	Part No.
Dana 30	http://arbusa.com/New_Products/differential_cover.pdf	0750002 ¹ *
Dana 35	http://arbusa.com/New_Products/differential_cover.pdf	0750004*
	¹ Will not work with stock height vehicles	
	*Internal diff cover modifications may be necessary with some R&P ratios if contact with cover occurs	

THULE ROOF RACK SYSTEM TO SUIT ARB ROOFTOP TENT
Year Model Description

YearModelDescriptionPart No.1993-98ZJThule roof rack system to suit ARB Rooftop tentTA50020

^{*} Firmer shock.

² Newer OEM Dana 35 & Dana 44 gear rings have 7/16" bolts. Flange holes of the Air Locker must be reamed larger to suit.

³ Some Dana 35's 4.10 gear sets, may require a high speed carrier air locker. (RD103)