


[Home](#) : [Sitemap](#) : [Help](#)
[Showroom](#)


Camry

Select Your Country

Hilux IMV A dynamic presence that integrates advanced power.

[Introduction](#) : [Highlights](#) : [Gallery](#) : [Specifications](#) : [Colour](#) : [Full Specs](#)

4X4/Pre runner Double Cab

Corolla	Corolla T Sport
Coaster 2004	Camry
RAV4	Echo
Land Cruiser 70	Land Cruiser
Land Cruiser 100	Hiace
Hilux IMV	Dyna
4Runner	Yaris
Lite Ace	Avensis
Avensis Verso	Tundra 2005
Tacoma	

[Goodies](#)
[Toyota Club](#)
[Motorsport](#)
[Technology](#)
[Environment](#)
[About Toyota](#)

Model grade	Pre-Runner TGN36L-PRPSKM	KUN26L-PRMSYM	KUN26L-PR
Dimensions & Vehicle Weight			
Overall Length (mm)	5255	5255	5255
Overall Width (mm)	1835	1835	1835
Overall Height *1 (mm)	1810	1810	1810
Wheelbase (mm)	3085	3085	3085
Tread Front (mm)	1540	1540	1540
Tread Rear (mm)	1540	1540	1540
Room Length (mm)	2130	2130	2130
Room Width (mm)	1475	1475	1475
Room Height (mm)	1195	1195	1195
Overhang Front (mm)	885	885	885
Overhang Rear (mm)	1285	1285	1285
Min. Running Ground Clearance (mm)	212	212	212
Angle of Approach (degrees)	30	30	30
Angle of Departure (degrees)	26	26	26
Curve Weight Front (kg)	905-915	1085-1095	1105-1115
Curve Weight Rear (kg)	745-755	755-765	760-770
Curve Weight Total (kg)	2670	2790	2790
Gross Vehicle Front (mm)	1130	1250	1240
Gross Vehicle Rear (mm)	1540	1540	1550
Gross Vehicle Total (mm)	2670	2790	2790
Deck floor to ground (mm)	855	855	855
Deck Height (mm)	450	450	450
Deck Length (mm)	1520	1520	1520
Deck Width (mm)	1515	1515	1515
Fuel Tank Capacity (L)	76	76	76
Engine			
Engine	2TR-FE	1KD-FTV	
No. of Cyls. & Arrangement	4-Cylinders, In-line	4-Cylinders, In-line	
Valve Mechanism	16-Valves, DOHC with VVT-i	16-Valves, DOHC	
Bore x Stroke (mm)	95.0 x 95.0	96.0 x 103	
Displacement (cm ³)	2694	2982	
Compression Ratio	9.6:1	17.9:1	
Fuel System	EFI	Common Rail Type	
Reserch Octane No. or Cetane No.	91 or Higher	50 or Higher	
Max. Output (Sae net) (kW/rpm)	118/5200	120/3400	
Max. Torque (Sae net) (Nm/_rpm)	241/3800	343/1400-3200	
Chassis			
Transmission Type	A343E (AT)	R151F (MT)	A340F (AT)
Transmission Gear Ratio 1st	2.804	4.313	2.804
Transmission Gear Ratio 2nd	1.531	2.330	1.531
Transmission Gear Ratio 3rd	1.000	1.436	1.000
Transmission Gear Ratio 4th	0.753	1.000	0.705
Transmission Gear Ratio 5th	-	0.838	-
Transmission Gear Ratio Reverse	2.393	4.220	2.393
Differential Gear ratio (Front/Rear)	-/4.555	3.583/3.583	3.727/3.727
Differential Ring Gear Size (Front/Rear) in.	-/8"	8"/8"	8"/8"
Brake Type Front	Ventilated Disc	Ventilated Disc	Ventilated Disc
Brake Type Rear	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum
Suspension Type Front	Double Wishbone	Double Wishbone	Double Wishbone
Suspension Type Rear	Leaf, Rigid	Leaf, Rigid	Leaf, Rigid
Stabilizer Bar (Front/Rear)	Standard/-	Standard/-	Standard/-
Steering Gear Type	Rack & Pinion	Rack & Pinion	Rack & Pinion
Steering Gear Ratio	19.4	19.4	19.4
Lock to Lock	3.82	3.72	3.72
Power Steering type	Integral Type	Integral Type	Integral Type

*1: Uni-Driven Vehicle

*2: With Flat Type Rear Bumper

