

STURACO[®] 7098

Friction Modifier

Application

Sturaco 7098 is a friction modifier to supplement sulfur-phosphorous gear oil additives for limited-slip performance.

Sturaco 7098 is a balanced additive formulated for use in conjunction with various lubricants. Mil-L-2105D/E gear oil for limited-slip characteristics use 2% to 5%:

Manual transaxles	3% - 5%
Engine oil for noise reduction	1% - 2%
Universal tractor fluids	2% - 4%

Data (typical values)

Specific Gravity 15.6°C	0.92
Viscosity @ 100°C	9.0 cSt
Phosphorous	1.50% by weight
Sulfur	0.80% by weight
Nitrogen	1.50% by weight

Advantages

- Excellent anti-chatter properties.
- Short term solution to wear caused by mechanical problems.
- Approval for use by major automotive manufacturers.
- Meets Ford M2C 118A specification.
- Meets Dana 40819 specification.
- Meets DaimlerChrysler MS 5630 specification.

Sturaco 7098 should be stored at ambient temperatures. Should the product be subjected to temperatures below 20°C, it should be warmed to ambient before use.

Normal hygiene practices should be used when handling **Sturaco 7098**. If skin contact occurs, wash affected areas thoroughly with soap and water. Use with adequate ventilation.

Refer to the MSDS for proper handling and disposal. Additional advice can also be obtained from your local D. A. Stuart representative.

NOTE:
Read and understand all precautions on container labels before using this product.

STURACO 7098

Headquarters:

4580 Weaver Parkway
Warrenville, IL 60555
Tel (630) 393-0833
Fax (630) 393-0834



D. A. Stuart Company

www.dastuart.com

Regional Office:

9100 Freeland Avenue
Detroit, MI 48228-2399
Tel (313) 273-7374
Fax (313) 838-1930