

XRC12

BY SMITTYBILT

The new Smittybilt XRC 12 is a 12,000 lb thoroughbred that has the looks and performance to handle any situation you get into. It is really the total package! We start off with one of the largest motors in its class - 4.8 State-of-the-Art Series Wound Motor and equip it with 3-stage planetary gear system with a 295.75:1 gear ratio that delivers lightning fast line speed. The XRC 12 is the next generation in winching technology!



4.8hp - 12V Motor

HANDHELD
REMOTE SWITCH

4-WAY ROLLER
FAIRLEAD

FEATURES OF WINCH 1200LBS

Rated Line Pull:	12000LBS
Winch Motor:	4.8hp
Control:	Remote Switch, 12ft/3.6m lead
Gear train:	3-Stage Planetary
Gear Reduction Ratio:	295.75:1
Clutch:	Sliding Ring Gear
Braking Action:	Automatic in-the-drum
Drum Size:	2.64" (67mm); 1.9" (228mm)
Cable:	Dia 3/8" (9.53mm) x 100'(30.5mm)
Fairlead:	4-way roller fairlead
Remote Control:	Included
Battery:	650CCA min. for winching
Battery Leads:	2 Gauge, 72" 183mm
Finish:	Black
Overall Dimensions:	21.57"x6.57"x11.77"
Mounting Bolt Pattern:	254mm x 114.3mm
G.W./N.W.:	43KGS/41KGS

LINE SPEED AND AMP DRAW (FIRST LAYER)

Line Pull	lbs	No	2000	4000	6000	8000	10000	12000
	kg	Load	907	1814	2721	3628	4536	5443
Line Speed	ft/min	38.9	16.3	12.3	10.4	8.6	5.8	5.6
	m/min	11.9	4.9	3.7	3.2	2.6	1.8	1.7
Motor	Amps	50	100	145	190	230	290	352

1000LBS LINE PULL AND CABLE CAPACITY

Layers of cable		1	2	3	4	5
Rated line pull per layer	lbs	12000	10200	8400	7300	6500
	kg	5443	4627	3810	3310	2948
Cumulative cable capacity	ft	15	38	64	95	100
	m	5	11.5	19.5	29	30.5

PART#

DESCRIPTION

97212 XRC12 12,000 lbs. Winch