


DANA® 60 STYLE

MODEL#	YEAR
DODGE® & PLYMOUTH®	
CARS W/HEMI	
ENGINES	66-72
CHEVROLET® C30/C35 (F)	77-95
CHEVROLET® C20/C25 (R)	80-92
CHRYSLER® 3/4 TON (F)	75-ON
CHRYSLER® 3/4 TON (R)	61-ON
CHRYSLER® 3/4 TON RAM®	
(REAR)	94-ON

MODEL#	YEAR
CHRYSLER® 1 TON (F)	75-ON
CHRYSLER® 1 TON (R)	57-ON
DODGE® W200/W250	
(F&R)	69-ON
FORD® E250-E350	82-92
FORD® F100 (R)	67-85
FORD® F250 (F&R)	67-92
FORD® F350 (F&R)	78-92
FORD® 3/4 TON (F)	73-79

MODEL#	YEAR
FORD® 3/4 TON (R)	54-ON
FORD® 1 TON (F)	79-98
FORD® 1 TON (F)	2000-ON
FORD® 1 TON (R)	54-ON
GM® 3/4 TON (R)	67-72
GM® 1 TON (F)	77-91
GM® 1 TON (R)	73-91
JEEP® J20 (R)	78-88
JEEP® CJ SERIES (R)	82-85



10-3/4" X 11-1/2"
10 HOLES
OVAL

R&P SUITABLE FOR DANA®/SPICER®				
MG#	DANA® # REAR AXLE	DANA® # FRONT AXLE	TEETH	RATIO
D60-354	706033-1X	706033-1X	46-13	3.54
700020-1		700020-1~	46-13	3.54
706033-15X	706033-15X	706033015X	39-11	3.55
708009-1*	708009-1*		39-11	3.55
708125-6**	708125-6**		39-11	3.55
D60-373	706033-2X	706033-2X	41-11	3.73
708125-4**	708125-4**		41-11	3.73
708021-1			45-11	4.09
D60-410	706033-3X	706033-3X	41-10	4.10
D60-410F~		700020-2~	41-10	4.10
708123-2^		708123-3-2^	41-10	4.10
708009-2*	708009-2*		41-10	4.10
708125-5**	708125-5**		41-10	4.10
708123-3^		708123-3^	43-10	4.30
D60-456	706033-4X	706033-4X	41-9	4.56
D60-456XF•			41-9	4.56
708123-4^		708123-4^	39-8	4.88
D60-488XF•			39-8	4.88
D60-513	706033-9X	706033-9X	41-8	5.13
D60-513XF•			41-8	5.13
D60-538			43-8	5.38
708123-5^		708123-5^	43-8	5.38
D60-538XF•			43-8	5.38
706033-6X	706033-6X	706033-6X	41-7	5.86

R&P SUITABLE FOR DANA®/SPICER® (cont'd)				
MG#	DANA® # REAR AXLE	DANA® # FRONT AXLE	TEETH	RATIO
706033-7X		706033-7X	37-6	6.17
706033-8X		706033-8X	43-6	7.17
~	REVERSE CUT - FRONT			
*	DODGE® ONLY - REAR			
**	FORD® ONLY - REAR			
^	FITS LATE 2000-UP - FORD® FRONT REVERSE			
•	REVERSE ROTATION THICK GEAR - FITS 4.10 & NUMERICALLY LOWER RATIO CASE			
DANA® SPICER Kits Include: R&P, bearings, shim, seal, gasket and ring bolts.				

SPECIFICATIONS:

- RG DIAMETER 9.75"
 - 12 1/2" X 18 RH THREADED BOLTS
 - PINION DIAMETER 1.626" 29 SPLINES
 - CASES: 4.10 & NUMERICALLY LOWER 4.56 & NUMERICALLY HIGHER
- 8620 Material - Heat Treated

MOTIVE GEAR® Part# is ring & pinion only.

MASTER KITS ALSO AVAILABLE (SEE NOTE #1, P. 3)
TIMKEN®MASTER KITS ALSO AVAILABLE (SEE NOTE #2, P. 3)

NOTE: WHILE WE HAVE MADE EVERY EFFORT TO INCLUDE
HELPFUL APPLICATION NOTES, WE RECOMMEND YOU
SPECIFY BILL OF MATERIAL WHEN ORDERING.

DANA® 60 STYLE INSTALLATION KITS & KIT COMPONENTS

DESCRIPTION	INSTALLATION KIT NO.	BEARING KIT NO.	MASTER KIT NO.	SUPER KIT NO.
1950-ON	D60IK	RA29R RA29RT*	RA28RMK RA29RMKT*	
2000-ON FRONT FORD®	D60IK	RA29RA RA29RAT*	RA29RAMK RA29RAMKT*	
1998-ON REAR	D60IK	RA29RL RA29RLT*	RA29RLMK RA29RLMKT*	

*KIT CONTAINS TIMKEN® BEARINGS

DESCRIPTION	PINION SHIMS	CARRIER SHIMS	CRUSH SLEEVE	PINION SEAL	PINION NUT	RING GEAR BOLT	COVER GASKET
DANA® 60	1110	1106	1118	6808N / 9316	30271	40638	5116